

Miniwash

AUTOMOTIVE HANDWASH UNIT

Hot and cold water at any location is now an affordable reality.

Kinetics Engineering is proud to release what is undoubtedly the most compact, easy to install and technologically advanced mobile handwash unit.

For anyone whose work brings them into contact with hazardous substances, or unhygienic conditions, it should be considered a necessity. Extensively used by Telstra Australia, Miniwash can assist you in meeting occupational health and safety requirements.

FEATURES

Miniwash features a single tap/single temperature operation, thermostatically controlled to 44°C. The system is also protected by a thermal overload safety device. Miniwash is ideal for small van applications and features a three way port drain.

1. Large Filler Opening

Allows easy filling

2. Water Level Indicator

3. Indicator Lamp

Illuminates when heater element is operating

4. Quality Taps

Quality hot tap, maintenance free

5. High Impact Housing

Moulded from super tough, UV resistant polymers suitable for internal and external applications

6. Fold Down Basin

Drains automatically when folded up

7. Drain Hose


Drain hose fitted to the base of the unit for dispersion of used water.

Easy Installation

Unit can easily be mounted to any vertical surface and wired to a 12 or 24 volt power source.



SPECIFICATIONS



Miniwash weight

4.4kg Empty, 10.3kg Full

Water capacity

6.0 litres

Voltage

Miniwash 12v System
– 9.6 Amps at 12 Volt DC

Miniwash 24v System
– 7 Amps at 24 Volt DC

- Hot tap only.
- Unit is thermostatically controlled.
- Unit has a Power lead (Red) & Earth lead (Red/Black Tracer).
- Earth Lead is connected to the vehicles chassis.
- Power lead connected to vehicles power supply via a relay, so unit is only operational when the vehicles ignition is on.